


Alem Track Lights

ITEM SKU#: 662187489742













Product Code: IK-RALEMTL-30W-30K-WH-90C-60D

| Voltage | 100 - 277 V AC, 50-60 Hz |
|--------------------|--------------------------|
| Lumen Output | 2733.3lm |
| Power | 30W |
| Efficacy | 140lm/w |
| ССТ | 3000K |
| CRI | >90 |
| Beam Angle | 60° |
| Light Distribution | Wide flood |
| LED Type | СОВ |
| LED Light Source | Bridgelux V13 |
| Start Time | Instant |
| Driver | IK-LKAD029DC-05242 |
| Operating Position | Swiveling Type |
| Dimming | 0-10V |
| Construction | Track |
| Mounting Type | Track Light Structure |
| Heads | Single Head |
| Body Material | Aluminium Die cast |
| Finish | White |
| Length | 5-1/2" |
| Height | 7-3/4" |
| Diameter | 3-1/2" |
| Application Area | Indoor Applications |
| | |

| Options) | |
|--|-------|
| edium <mark>24°</mark> Flood <mark>38°</mark> Wide Flood | 60° |
| t Ø ft Ø ft | Ø |
| 3.0 1.41 3.0 2.03 3.0 | 3.15 |
| 9.0 4.22 9.0 6.09 9.0 | 9.45 |
| 5.0 7.04 15.0 10.15 15.0 | 15.75 |
| 8.0 1.41 3.0 2.03 3.0 9.0 4.22 9.0 6.09 9.0 | |

Alem is a technologically advanced LED track light with incorporated electronic gear and chip on board.It also has a high-quality reflector with three different beam spreads. Moreover, the lamp housing of die-cast aluminium for optimal cooling allows the fixture to last longer than its traditional counterparts.

Technical Data

IES File Link 丛

Installation Instructions Link 🕹

