




### Product Code : IK-TLS3-33W-40K-38D-BL-HT

|                    |                           |
|--------------------|---------------------------|
| Voltage            | 100-277V                  |
| Lumen Output       | 950lm                     |
| Power              | 33W                       |
| Efficacy           | 95lm/w                    |
| CCT                | 3500K                     |
| CRI                | 82                        |
| Beam Angle         | 38°                       |
| Light Distribution | Wide                      |
| LED Type           | COB                       |
| Dimming            | 120-Triac/ELV 277- No Dim |
| Mounting Type      | Track Light Structure     |
| Heads              | Single Head               |
| Body Material      | Aluminum                  |
| Finish             | Black                     |
| Length             | 6.57"                     |
| Height             | 1.01"                     |
| Diameter           | 3.48"                     |
| IP Rating          | IP20                      |
| Cover Material     | Polycarbonate             |

#### Beam Spread (Options)

| Spot | 15°  | Medium | 24°  | Wide | 38°   | Ultrawide | 60°   |
|------|------|--------|------|------|-------|-----------|-------|
| ft   | Ø    | ft     | Ø    | ft   | Ø     | ft        | Ø     |
| 3.0  | 0.72 | 3.0    | 1.41 | 3.0  | 2.03  | 3.0       | 1.02  |
| 9.0  | 2.15 | 9.0    | 4.22 | 9.0  | 6.09  | 9.0       | 9.45  |
| 15.0 | 3.58 | 15.0   | 7.04 | 15.0 | 10.15 | 15.0      | 15.75 |

Aureo offers professional grade lighting with a sleek form that complements any modern space. Designed for adaptability, it creates ambience, highlights displays, and transforms layouts with ease. Aureo combines efficiency with reliability, delivering consistent brightness while conserving energy. Perfect for retail, hospitality, or commercial applications, this track head merges performance with refined style, offering an ideal balance of function, design, and versatility.