



Product Code : IK-WLS9-12IN-40W-5CCT-BL-PC

| | |
|--------------------|--|
| Voltage | 120-347V |
| Lumen Output | 3400lm |
| Power | 40W |
| Efficacy | 85lm/w |
| CCT Selectable(K) | 2700-3000-3500-4000-5000K |
| CRI | 90 |
| Beam Angle | 10-25-30-45-60° |
| Light Distribution | Ultrawide |
| Dimming | 0-10V Dimming |
| Body Material | Aluminium |
| Finish | Black |
| Length | 4.7" |
| Height | 11.8" |
| IP Rating | IP65 |
| Cover Material | High light transmittance Polycarbonate |
| Width (W) | 5.9" |

Beam Spread (Options)

| Spot | 10° | Medium | 25° | Wide | 30° | Ultrawide | 45° | Ultrawide | 60° |
|------|------|--------|-------|-------|-------|-----------|-------|-----------|-------|
| ft | 3.0 | 3.0 | 3.0 | 3.0 | 3.0 | 3.0 | 3.0 | 3.0 | 3.0 |
| ft | 0.72 | 1.41 | 2.03 | 2.03 | 1.02 | 1.02 | 1.02 | 1.02 | 1.02 |
| ft | 2.15 | 4.22 | 6.09 | 6.09 | 9.45 | 9.45 | 9.45 | 9.45 | 9.45 |
| ft | 3.58 | 7.04 | 10.15 | 10.15 | 15.75 | 15.75 | 15.75 | 15.75 | 15.75 |

Aurell offers clean, modern downlighting designed for flexibility and precision. Its slim profile fits seamlessly into interiors, while smooth adjustability makes it ideal for accenting details or refreshing layouts. Built with durable die-cast aluminum, it delivers long-term reliability and efficient thermal performance. Perfect for commercial, or institutional environments, Aurell blends functionality and elegance, providing dependable illumination with a sleek, contemporary look that adapts effortlessly.



COB LED



DIMMABLE



IP20