


Cline Wall Sconces



Product Code : IK-WLS9-12IN-40W-5CCT-BL-PC

Voltage	120-347V
Lumen Output	3400lm
Power	40W
Efficacy	85lm/w
CCT Selectable(K)	2700-3000-3500-4000-5000K
CRI	90
Beam Angle	10-25-30-45-60°
Light Distribution	Ultrawide
Dimming	0-10V Dimming
Body Material	Aluminium
Finish	Black
Length	4.7"
Height	11.8"
IP Rating	IP65
Cover Material	High light transmittance Polycarbonate
Width (W)	5.9"

Beam Spread (Options)

Spot	10°	Medium	25°	Wide	30°	Ultrawide	45°	Ultrawide	60°
ft	0.72	3.0	1.41	3.0	2.03	3.0	1.02	3.0	1.02
9.0	2.15	9.0	4.22	9.0	6.09	9.0	9.45	9.0	9.45
15.0	3.58	15.0	7.04	15.0	10.15	15.0	15.75	15.0	15.75

Aureli offers clean, modern downlighting designed for flexibility and precision. Its slim profile fits seamlessly into interiors, while smooth adjustability makes it ideal for accenting details or refreshing layouts. Built with durable die-cast aluminum, it delivers long-term reliability and efficient thermal performance. Perfect for commercial, or institutional environments, Aureli blends functionality and elegance, providing dependable illumination with a sleek, contemporary look that adapts effortlessly.

