



Product Code : IK-RLUMOSDL-15W-35K-BL-90C-15D

Voltage	100 - 277 V AC, 50-60 Hz
Lumen Output	1378.12lm
Power	15W
Efficacy	140lm/w
CCT	3500K
CRI	>90
Beam Angle	15°
Light Distribution	Spot
LED Light Source	Osram SOLERIQ S 19
Start Time	Instant
Driver	Stand Alone (included)
Operating Position	Non - Swiveling Type
Dimming	On-Off / Triac / 0-10 V
Construction	Round
Mounting Type	Recessed
Heads	Single Head
Body Material	Aluminium Die cast
Finish	Black
Height	4-7/8"
Diameter	4-1/2"
Cut Out	4-1/8"
Optics	Darklight Technology Black, Silver
Application Area	Guest Room, Corridor, Restaurant, Meeting Room Club, Hall, Hotel Entrance

Beam Spread (Options)

Spot 15°	Medium 24°	Flood 38°	Wide Flood 60°
ft	ft	ft	ft
3.0	3.0	3.0	3.0
0.72	1.41	2.03	3.15
9.0	4.22	6.09	9.45
15.0	7.04	10.15	15.75

Circular in design, this LED downlight is made up of aluminum die cast with high quality powder coated luminaire housing and optimum heat sink. Available in multiple wattages and beam angle, the luminaire renders greater flexibility in its application for store lighting. Moreover, the specular darklight reflector in this store light allows outstanding visual comfort to the visitors.

Technical Data

↓ IES File Link

↓ Installation Instructions Link