



### Product Code : IK-ROCULDL-08W-30K-WH-90C-36D

|                    |   |
|--------------------|---|
| Voltage            | 100 - 277 V AC, 50-60 Hz                    |
| Lumen Output       | 1264lm                                      |
| Power              | 8W  |
| Efficacy           | 140lm/w                                     |
| CCT                | 3000K                                       |
| CRI                | >90   |
| Beam Angle         | 36°   |
| Light Distribution | Flood                                       |
| LED Type           | COB   |
| LED Light Source   | Osram SOLERIQ S 19                          |
| Start Time         | Instant                                     |
| Driver             | Stand Alone (included)                      |
| Operating Position | Non - Swiveling Type                        |
| Dimming            | On-Off / Triac / 0-10 V                     |
| Construction       | Round                                       |
| Mounting Type      | Recessed                                    |
| Heads              | Single Head                                 |
| Body Material      | Aluminium Die cast                          |
| Finish             | White                                       |
| Height             | 2-3/8"                                      |
| Diameter           | 3-1/2"                                      |
| Cut Out            | 3"  |
| Optics             | Darklight Technology Black, Silver          |
| Application Area   | Classroom, Meeting Room, Office, Club, Home |

#### Beam Spread (Options)

| Spot | 15°  | Medium | 24°  | Flood | 36°   | Wide Flood | 60°   |
|------|------|--------|------|-------|-------|------------|-------|
| ft   | Ø    | ft     | Ø    | ft    | Ø     | ft         | Ø     |
| 3.0  | 0.72 | 3.0    | 1.41 | 3.0   | 2.03  | 3.0        | 3.15  |
| 9.0  | 2.15 | 9.0    | 4.22 | 9.0   | 6.09  | 9.0        | 9.45  |
| 15.0 | 3.58 | 15.0   | 7.04 | 15.0  | 10.15 | 15.0       | 15.75 |

Ocul, a round shaped LED downlight made of aluminum die cast with high quality powder coated luminaire housing and optimum heat sink. Specular reflector & power grid /global connectors available with isolated LED Driver using Ultra bright OSRAM COB.