


Olivio Down Lights















Product Code: IK-ROLIVIODL-8W-27K-BL-90C-15D

Voltage	100 - 277 V AC, 50-60 Hz				
Lumen Output	644.85lm				
Power	8W				
Efficacy	140lm/w				
CCT	2700K				
CRI	>90				
Beam Angle	15°				
Light Distribution	Spot				
LED Type	COB				
LED Light Source	Osram SOLERIQ S 19				
Start Time	Instant				
Driver	Stand Alone (included)				
Operating Position	Non - Swiveling Type				
Dimming	On-Off / Triac / 0-10 V				
•					
Construction	Round				
-	Round Recessed				
Construction					
Construction Mounting Type	Recessed				
Construction Mounting Type Heads	Recessed Single Head				
Construction Mounting Type Heads Body Material	Recessed Single Head Aluminium Die cast				
Construction Mounting Type Heads Body Material Finish	Recessed Single Head Aluminium Die cast Black				
Construction Mounting Type Heads Body Material Finish Height	Recessed Single Head Aluminium Die cast Black 4"				
Construction Mounting Type Heads Body Material Finish Height Diameter	Recessed Single Head Aluminium Die cast Black 4" 6-1/2"				

Beam Spread (Options)								
Spot	15°	Medium	24°	Flood	38°	Wide Fl	ood 60°	
ft	Ø	ft	Ø	ft	Ø	ft	Ø	
3.0	0.72	3.0	1.41	3.0	2.03	3.0	3.15	
9.0	2.15	9.0	4.22	9.0	6.09	9.0	9.45	
15.0	3.58	15.0	7.04	15.0	10.15	15.0	15.75	

Olivio, a round LED downlight made of aluminum die cast with high quality powder coated luminaire housing and optimum heat sink. Specular reflector & power grid /global connectors available with isolated LED Driver using Ultra bright OSRAM COB.

Technical Data

IES File Link <u>⊀</u>

Installation Instructions Link 🕹

