


Olivio Down Lights

ITEM SKU#: 662187498195













Product Code: IK-ROLIVIODL-8W-27K-BL-90C-24D

Voltage	100 - 277 V AC, 50-60 Hz			
Lumen Output	648.38lm			
Power	8W			
Efficacy	140lm/w			
CCT	2700K			
CRI	>90			
Beam Angle	24°			
Light Distribution	Medium			
LED Type	COB			
LED Light Source	Osram SOLERIQ S 19			
Start Time	Instant			
Driver	Stand Alone (included)			
Operating Position	Non - Swiveling Type			
Dimming	On-Off / Triac / 0-10 V			
Construction	Round			
Construction Mounting Type	Round			
Mounting Type	Recessed			
Mounting Type Heads	Recessed Single Head			
Mounting Type Heads Body Material	Recessed Single Head Aluminium Die cast			
Mounting Type Heads Body Material Finish	Recessed Single Head Aluminium Die cast Black			
Mounting Type Heads Body Material Finish Height	Recessed Single Head Aluminium Die cast Black 4"			
Mounting Type Heads Body Material Finish Height Diameter	Recessed Single Head Aluminium Die cast Black 4" 6-1/2"			

Beam Spread (Options)								
Spot	15°	Medium	24°	Flood	38°	Wide Fl	ood 60°	
ft	Ø	ft	Ø	ft	Ø	ft	Ø	
3.0	0.72	3.0	1.41	3.0	2.03	3.0	3.15	
9.0	2.15	9.0	4.22	9.0	6.09	9.0	9.45	
15.0	3.58	15.0	7.04	15.0	10.15	15.0	15.75	

Olivio, a round LED downlight made of aluminum die cast with high quality powder coated luminaire housing and optimum heat sink. Specular reflector & power grid /global connectors available with isolated LED Driver using Ultra bright OSRAM COB.

Technical Data

IES File Link <u>⊀</u>

Installation Instructions Link 🕹

