


## Olivio Down Lights















## Product Code: IK-ROLIVIODL-8W-35K-WH-90C-24D

Voltage	100 - 277 V AC, 50-60 Hz
Lumen Output	714.84lm
Power	8W
Efficacy	140lm/w
CCT	3500K
CRI	>90
Beam Angle	24°
Light Distribution	Medium
LED Type	СОВ
LED Light Source	Osram SOLERIQ S 19
Start Time	Instant
Driver	Stand Alone (included)
Operating Position	Non - Swiveling Type
Dimming	On-Off / Triac / 0-10 V
Dimming  Construction	On-Off / Triac / 0-10 V Round
-	
Construction	Round
Construction  Mounting Type	Round Recessed
Construction  Mounting Type  Heads	Round Recessed Single Head
Construction  Mounting Type  Heads  Body Material	Round Recessed Single Head Aluminium Die cast
Construction  Mounting Type  Heads  Body Material  Finish	Round Recessed Single Head Aluminium Die cast White
Construction  Mounting Type  Heads  Body Material  Finish  Height	Round Recessed Single Head Aluminium Die cast White 4"
Construction  Mounting Type  Heads  Body Material  Finish  Height  Diameter	Round Recessed Single Head Aluminium Die cast White 4" 6-1/2"

Beam Spread (Options)								
15°	Medium	24°	Flood	38°	Wide Fl	ood 60°		
Ø	ft	Ø	ft	Ø	ft	Ø		
0.72	3.0	1.41	3.0	2.03	3.0	3.15		
2.15	9.0	4.22	9.0	6.09	9.0	9.45		
3.58	15.0	7.04	15.0	10.15	15.0	15.75		
	0.72 2.15	15° Medium Ø ft 0.72 3.0 2.15 9.0	15° Medium 24° Ø ft Ø 0.72 3.0 1.41 2.15 9.0 4.22	15° Medium 24° Flood  Ø ft Ø ft  0.72 3.0 1.41 3.0 2.15 9.0 4.22 9.0	15°   Medium   24°   Flood   38°	15°   Medium   24°   Flood   38°   Wide Flood   07°   07°   30°   1.41   30°   2.03   30°   2.15   9.0   4.22   9.0   6.09   9.0		

Olivio, a round LED downlight made of aluminum die cast with high quality powder coated luminaire housing and optimum heat sink. Specular reflector & power grid (global connectors available with isolated LED Driver using Ultra bright OSRAM COB.

## **Technical Data**

IES File Link <u>⊀</u>

Installation Instructions Link 🕹

