



### Product Code : IK-RTHEIADL-15W-30K-BL-90C-15D

Voltage	100 - 277 V AC, 50-60 Hz
Lumen Output	1312.5lm
Power	15W
Efficacy	140lm/w
CCT	3000K
CRI	>90
Beam Angle	15°
Light Distribution	Spot
LED Type	COB
LED Light Source	Osram SOLERIQ S 19
Start Time	Instant
Driver	Stand Alone (included)
Operating Position	Non - Swiveling Type
Dimming	On-Off / Triac / 0-10 V
Construction	Sqaure
Mounting Type	Recessed
Heads	Single Head
Body Material	Aluminium Die cast
Finish	Black
Length	3-3/4"
Height	5-1/8"
Cut Out	3-7/8"
Optics	Darklight Technology Black, Silver
Width (W)	3-3/4"
Application Area	Guest Room, Corridor, Restaurant, Meeting Room Club, Hall, Hotel Entrance

#### Beam Spread (Options)

Spot 15°	Medium 24°	Flood 38°	Wide Flood 60°
ft	ft	ft	ft
0.72	1.41	2.03	3.15
2.15	4.22	6.09	9.45
3.58	7.04	10.15	15.75

Theia, a square LED downlight made of aluminum die cast with high quality powder coated luminaire housing and optimum heat sink. Specular reflector & power grid / global connectors available with isolated LED Driver using Ultra bright OSRAM COB.

### Technical Data

↓ IES File Link