



Product Code : IK-RFLARED L-40W-27K-BL-90C-60D

| | |
|--------------------|------------------------------------|
| Voltage | 100 - 277 V AC, 50-60 Hz |
| Lumen Output | 3600lm |
| Power | 40W |
| Efficacy | 90lm/w |
| CCT | 2700K |
| CRI | >90 |
| Beam Angle | 60° |
| Light Distribution | Wide flood |
| LED Light Source | Osram SOLERIQ S 19 |
| Start Time | Instant |
| Driver | Stand Alone (included) |
| Operating Position | Non - Swiveling Type |
| Dimming | On-Off / Triac / 0-10 V |
| Construction | Sqaure |
| Mounting Type | Recessed |
| Heads | Single Head |
| Finish | Black |
| Height | 3" |
| Diameter | 8-1/4"x8-1/4" |
| Cut Out | 7-1/2"x7-1/2" |
| Optics | Darklight Technology Black, Silver |
| Application Area | Outdoor Corridor, Bathroom, Eave. |



Beam Spread (Option)

| Wide Flood | 60° |
|------------|-------|
| ft | Ø |
| 3.0 | 3.15 |
| 9.0 | 9.45 |
| 15.0 | 15.75 |

Flare downlight is a square shaped fixture, that illuminates a store in the most effective manner without being obtrusive. The smart engineering of the luminaire with specular reflector & power grid/global connectors along with high voltage standing in-house LED driver makes it an ideal choice for lighting your stores.