



Product Code : IK-ROPTIKTL-15W-30/40/50K-BL-90C-ADB

Voltage	100 - 277 V AC, 50-60 Hz
Lumen Output	1359lm
Power	15W
Efficacy	90lm/w
CCT Selectable(K)	3000- 4000- 5000K
CRI	>90
Beam Angle	15°
Light Distribution	Wide flood
LED Type	COB
LED Light Source	Osram SOLERIQ S 19
Start Time	Instant
Driver	Built in
Operating Position	Swiveling Type
Dimming	Triac Dimming
Construction	Track
Mounting Type	Track Light Structure
Heads	Single Head
Body Material	Aluminium Die cast
Finish	Black
Length	6-1/4"
Height	6-3/4"
Diameter	2-1/2"
Application Area	Indoor Applications

Beam Spread (Options)

Spot	15°	Medium	24°	Flood	36°	Wide Flood	60°
ft	Ø	ft	Ø	ft	Ø	ft	Ø
3.0	0.72	3.0	1.41	3.0	2.03	3.0	3.15
9.0	2.15	9.0	4.22	9.0	6.09	9.0	9.45
15.0	3.58	15.0	7.04	15.0	10.15	15.0	15.75

Technical Data

↓ IES File Link

↓ Installation Instructions Link