




ITEM SKU#: IKTLS410W5CCT60DSL













## Product Code: IK-TLS4-10W-5CCT-60D-SL

Lumen Output1000lmPower10WEfficacy100lm/wCCT Selectable(K)2700-3000-3500-4000-5000KCRI90Beam Angle60°Light DistributionUltrawideLED TypeCOBLED Light SourceBridgeluxDimmingTriacMounting TypeTrack Light StructureHeadsSingle HeadBody MaterialAluminumFinishSilverHeight6.3"Diameter2.9"Cover MaterialPMMAWeight1.1	Voltage	120V
Efficacy 100lm/w  CCT Selectable(K) 2700-3000-3500-4000-5000K  CRI 90  Beam Angle 60°  Light Distribution Ultrawide  LED Type COB  LED Light Source Bridgelux  Dimming Triac  Mounting Type Track Light Structure  Heads Single Head  Body Material Aluminum  Finish Silver  Height 6.3"  Diameter 2.9"  Cover Material PMMA	Lumen Output	1000lm
CCT Selectable(K)  CRI  90  Beam Angle  Light Distribution  LED Type  COB  LED Light Source  Dimming  Triac  Mounting Type  Track Light Structure  Heads  Body Material  Finish  Silver  Height  Diameter  2.9"  Cover Material  PMMA	Power	10W
CRI 90 Beam Angle 60° Light Distribution Ultrawide  LED Type COB  LED Light Source Bridgelux  Dimming Triac  Mounting Type Track Light Structure  Heads Single Head  Body Material Aluminum  Finish Silver  Height 6.3"  Diameter 2.9"  Cover Material PMMA	Efficacy	100lm/w
Beam Angle 60° Light Distribution Ultrawide LED Type COB LED Light Source Bridgelux Dimming Triac Mounting Type Track Light Structure Heads Single Head Body Material Aluminum Finish Silver Height 6.3" Diameter 2.9" Cover Material PMMA	CCT Selectable(K)	2700-3000-3500-4000-5000K
Light Distribution  LED Type  COB  LED Light Source  Bridgelux  Dimming  Triac  Mounting Type  Track Light Structure  Heads  Single Head  Body Material  Finish  Silver  Height  6.3"  Diameter  2.9"  Cover Material  PMMA	CRI	90
LED TypeCOBLED Light SourceBridgeluxDimmingTriacMounting TypeTrack Light StructureHeadsSingle HeadBody MaterialAluminumFinishSilverHeight6.3"Diameter2.9"Cover MaterialPMMA	Beam Angle	60°
LED Light Source  Dimming  Triac  Mounting Type  Track Light Structure  Heads  Single Head  Body Material  Aluminum  Finish  Silver  Height  6.3"  Diameter  2.9"  Cover Material  PMMA	Light Distribution	Ultrawide
Dimming Triac  Mounting Type Track Light Structure  Heads Single Head  Body Material Aluminum  Finish Silver  Height 6.3"  Diameter 2.9"  Cover Material PMMA	LED Type	COB
Mounting Type Track Light Structure  Heads Single Head  Body Material Aluminum  Finish Silver  Height 6.3"  Diameter 2.9"  Cover Material PMMA	LED Light Source	Bridgelux
Heads Single Head  Body Material Aluminum  Finish Silver  Height 6.3"  Diameter 2.9"  Cover Material PMMA	Dimming	Triac
Body Material Aluminum  Finish Silver  Height 6.3"  Diameter 2.9"  Cover Material PMMA	Mounting Type	Track Light Structure
Finish Silver Height 6.3"  Diameter 2.9"  Cover Material PMMA	Heads	Single Head
Height 6.3"  Diameter 2.9"  Cover Material PMMA	Body Material	Aluminum
Diameter 2.9"  Cover Material PMMA	Finish	Silver
Cover Material PMMA	Height	6.3"
	Diameter	2.9"
Weight 1.1	Cover Material	PMMA
	Weight	1.1

Beam :	Sprea	d (Optio	ns)		
Medium 24°		Wide 30°		Ultrawide 60°	
ft	Ø	ft	Ø	ft	Ø
3.0	0.72	3.0	1.41	3.0	2.03
9.0	2.15	9.0	4.22	9.0	6.09
15.0	3.58	15.0	7.04	15.0	10.15

This sleek track light blends adaptability and style, making it ideal for architectural and commercial interiors. Its slim form fits effortlessly into modern spaces while delivering consistent, bright illumination. Perfect for displays, offices, or retail environments, Optivus supports smooth dimming and precise adjustments. A versatile solution for projects needing both functional brightness and refined aesthetics, it simplifies planning without compromising on ambience or impact.

