




ITEM SKU#: IKTLS420W5CCT30DWH













Product Code: IK-TLS4-20W-5CCT-30D-WH

Lumen Output2000lmPower20WEfficacy100lm/wCCT Selectable(K)2700K-3000K-3500K-4000K-5000KCRI90Beam Angle30°Light DistributionFloodLED TypeCOBLED Light SourceBridgeluxDimmingTriacMounting TypeTrack Light StructureHeadsSingle HeadBody MaterialAluminumFinishWhiteHeight10.3"Diameter3.3"Cover MaterialPMMAWeight1.76	Voltage	120V			
Efficacy 100lm/w CCT Selectable(K) 2700K-3000K-3500K-4000K-5000K CRI 90 Beam Angle 30° Light Distribution Flood LED Type COB LED Light Source Bridgelux Dimming Triac Mounting Type Track Light Structure Heads Single Head Body Material Aluminum Finish White Height 10.3" Diameter 3.3" Cover Material PMMA	Lumen Output	2000lm			
CCT Selectable(K) CRI 90 Beam Angle Light Distribution LED Type COB LED Light Source Bridgelux Dimming Triac Mounting Type Track Light Structure Heads Single Head Body Material Finish White Height Diameter 3.3" Cover Material PMMA	Power	20W			
CRI 90 Beam Angle 30° Light Distribution Flood LED Type COB LED Light Source Bridgelux Dimming Triac Mounting Type Track Light Structure Heads Single Head Body Material Aluminum Finish White Height 10.3" Diameter 3.3." Cover Material PMMA	Efficacy	100lm/w			
Beam Angle30°Light DistributionFloodLED TypeCOBLED Light SourceBridgeluxDimmingTriacMounting TypeTrack Light StructureHeadsSingle HeadBody MaterialAluminumFinishWhiteHeight10.3"Diameter3.3"Cover MaterialPMMA	CCT Selectable(K)	2700K-3000K-3500K-4000K-5000K			
Light Distribution LED Type COB LED Light Source Bridgelux Dimming Triac Mounting Type Track Light Structure Heads Single Head Body Material Aluminum Finish White Height 10.3" Diameter Cover Material Flood Flood AUM Flood AUM Flood Flood Bridgelux Aum Triac Tr	CRI	90			
LED TypeCOBLED Light SourceBridgeluxDimmingTriacMounting TypeTrack Light StructureHeadsSingle HeadBody MaterialAluminumFinishWhiteHeight10.3"Diameter3.3"Cover MaterialPMMA	Beam Angle	30°			
LED Light SourceBridgeluxDimmingTriacMounting TypeTrack Light StructureHeadsSingle HeadBody MaterialAluminumFinishWhiteHeight10.3"Diameter3.3"Cover MaterialPMMA	Light Distribution	Flood			
DimmingTriacMounting TypeTrack Light StructureHeadsSingle HeadBody MaterialAluminumFinishWhiteHeight10.3"Diameter3.3"Cover MaterialPMMA	LED Type	COB			
Mounting TypeTrack Light StructureHeadsSingle HeadBody MaterialAluminumFinishWhiteHeight10.3"Diameter3.3"Cover MaterialPMMA	LED Light Source	Bridgelux			
Heads Single Head Body Material Aluminum Finish White Height 10.3" Diameter 3.3" Cover Material PMMA	Dimming	Triac			
Body Material Aluminum Finish White Height 10.3" Diameter 3.3" Cover Material PMMA	Mounting Type	Track Light Structure			
Finish White Height 10.3" Diameter 3.3" Cover Material PMMA	Heads	Single Head			
Height 10.3" Diameter 3.3" Cover Material PMMA	Body Material	Aluminum			
Diameter 3.3" Cover Material PMMA	Finish	White			
Cover Material PMMA	Height	10.3"			
	Diameter	3.3"			
Weight 1.76	Cover Material	PMMA			
	Weight	1.76			

Beam Spread (Options)

М	edium	24°	Flood	30°	Wide F	lood 60°
f	t	Ø	ft	Ø	ft	Ø
3	3.0	0.72	3.0	1.41	3.0	2.03
9	9.0	2.15	9.0	4.22	9.0	6.09
1	5.0	3.58	15.0	7.04	15.0	10.15

This sleek track light blends adaptability and style, making it ideal for architectural and commercial interiors. Its slim form fist effortlessly into modern spaces while delivering consistent, bright illumination. Perfect for displays, offices, or retail environments, Opitus supports smooth dimming and precise adjustments. A versatile solution for projects needing both functional brightness and refined aesthetics, it simplifies planning without compromising on ambience or impact.

