



## Product Code : IK-TLS4-30W-5CCT-24D-BL

Voltage	120V
Lumen Output	3000lm
Power	30W
Efficacy	100lm/w
CCT Selectable(K)	2700K-3000K-3500K-4000K-5000K
CRI	90
Beam Angle	24°
Light Distribution	Medium
LED Type	COB
LED Light Source	Bridgelux
Dimming	Triac
Mounting Type	Track Light Structure
Heads	Single Head
Body Material	Aluminum
Finish	Black
Height	8.01"
Diameter	3.01"
Cover Material	PMMA
Weight	1.76

### Beam Spread (Options)

Medium 24°		Flood 30°		Wide Flood 60°	
ft	Ø	ft	Ø	ft	Ø
3.0	0.72	3.0	1.41	3.0	2.03
9.0	2.15	9.0	4.22	9.0	6.09
15.0	3.58	15.0	7.04	15.0	10.15

This sleek track light blends adaptability and style, making it ideal for architectural and commercial interiors. Its slim form fits effortlessly into modern spaces while delivering consistent, bright illumination. Perfect for displays, offices, or retail environments. Optivus supports smooth dimming and precise adjustments. A versatile solution for projects needing both functional brightness and refined aesthetics, it simplifies planning without compromising on ambience or impact.

