


ITEM SKU#: 662187490588











Product Code: IK-RORKTL-30W-40K-WH-90C-ADB

| Voltage | 100 - 277 V AC, 50-60 Hz | | |
|--------------------|--------------------------|--|--|
| Lumen Output | 4200lm | | |
| Power | 30W | | |
| Efficacy | 140lm/w | | |
| ССТ | 4000K | | |
| CRI | >90 | | |
| Beam Angle | 15° | | |
| Light Distribution | Wide flood | | |
| LED Type | COB | | |
| LED Light Source | Osram SOLERIQ S 19 | | |
| Start Time | Instant | | |
| Driver | Stand Alone (included) | | |
| Operating Position | Swiveling Type | | |
| Dimming | Triac Dimming | | |
| Construction | Track | | |
| Mounting Type | Track Light Structure | | |
| Heads | Single Head | | |
| Body Material | Aluminium Die cast | | |
| Finish | White | | |
| Length | 7-1/8" | | |
| Height | 7-1/4" | | |
| Diameter | 3" | | |
| Cut Out | 7-3/8" | | |
| Width (W) | 7-3/8" | | |
| Application Area | Indoor Applications | | |
| | | | |

| Beam Spread (Options) | | | | | | | |
|-----------------------|------|--------|------|-------|-------|---------|---------|
| Spot | 15° | Medium | 24° | Flood | 36° | Wide Fl | ood 60° |
| ft | Ø | ft | Ø | ft | Ø | ft | Ø |
| 3.0 | 0.72 | 3.0 | 1.41 | 3.0 | 2.03 | 3.0 | 3.15 |
| 9.0 | 2.15 | 9.0 | 4.22 | 9.0 | 6.09 | 9.0 | 9.45 |
| 15.0 | 3.58 | 15.0 | 7.04 | 15.0 | 10.15 | 15.0 | 15.75 |

Ork is a technologically advanced LED track light with incorporated electronic gear and chip on board. It also has a high-quality reflector with three different beam spreads. Moreover, the lamp housing of die-cast aluminum for optimal cooling allows the fixture to last longer than its traditional counterparts.

Technical Data

▲ IES File Link

