


ITEM SKU#: 662187502021



COB LED

Product Code : IK-RAuroraPL-8W-50K-BL-90C-15D

VoltageI00 - 277 V AC, 50-60 HzLumen Outputu760lmPower8WPower800KCCT5000KCRI>90Beam Angle15°Light DistributionSpotIcD Light SourceOrsam SOLERIQ S 19Start TimeInstantDriverSchad Alone (included)Operating PositionNo Swiveling TypeImmingTriac Dimming / 0-10 V DimmingHeadsSingle HeadHeight5-7/8"Diameter3"OpticsReflective Cup StructureApplication AreaGuest Room, Restaurant, Meeting Room, Club, Hall, Hotel Entrance		
Power8WPower800KCCT5000KCRI>90Beam Angle15°Light DistributionSpotLED Light SourceOsram SOLERIQ S 19Start TimeInstantDriverStand Alone (included)Operating PositioNo Swiveling TypeImmingTriac Dimming / 0-10 V DimmingHeadsSingle HeadFinishBlackInimeter5-7/8"Diameter3"OpticsReflective Cup Structure	Voltage	100 - 277 V AC, 50-60 Hz
FinancialFinancialCCT5000KCRI>90Beam Angle15°Light DistributionSpotLED Light SourceOsram SOLERIQ S 19Start TimeInstantDriverStand Alone (included)Operating PositionNo Swiveling TypeImmingTriac Dimming / 0-10 V DimmingHeadsSingle HeadFinishBlackHeight5-7/8"Diameter3"OpticsReflective Cup Structure	Lumen Output	760lm
RRCRI>90Beam Angle15°Light DistributionSpotLED Light SourceOsram SOLERIQ S 19Start TimeInstantDriverStand Alone (included)Operating PositionNo Swiveling TypeDimmingTriac Dimming / 0-10 V DimmingHeadsSingle HeadFinishBlackHeight5-7/8"Diameter3"OpticsReflective Cup Structure	Power	8W
Beam AngleIs°Light DistributionSpotLED Light SourceOsram SOLERIQ S 19Start TimeInstantDriverStand Alone (included)Operating PositionNo Swiveling TypeDimmingTriac Dimming / 0-10 V DimmingHeadsSingle HeadFinishBlackHeightS-7/8"Diameter3"OpticsReflective Cup Structure	ССТ	5000K
Light DistributionSpotLED Light SourceOsram SOLERIQ S 19Start TimeInstantDriverStand Alone (included)Operating PositionNo Swiveling TypeDimmingTriac Dimming / 0-10 V DimmingHeadsSingle HeadFinishBlackHeight5-7/8"Diameter3"OpticsReflective Cup Structure	CRI	>90
LED Light SourceOsram SOLERIQ S 19Start TimeInstantDriverStand Alone (included)Operating PositionNo Swiveling TypeDimmingTriac Dimming / 0-10 V DimmingHeadsSingle HeadFinishBlackHeight5-7/8"Diameter3"OpticsReflective Cup Structure	Beam Angle	15°
Start TimeInstantDriverStand Alone (included)Operating PositionNo Swiveling TypeDimmingTriac Dimming / 0-10 V DimmingHeadsSingle HeadFinishBlackHeight5-7/8"Diameter3"OpticsReflective Cup Structure	Light Distribution	Spot
DriverStant Alone (included)Operating PositionNo Swiveling TypeDimmingTriac Dimming / 0-10 V DimmingHeadsSingle HeadFinishBlackHeight5-7/8"Diameter3"OpticsReflective Cup Structure	LED Light Source	Osram SOLERIQ S 19
Operating PositionNo Swiveling TypeDimmingTriac Dimming / 0-10 V DimmingHeadsSingle HeadFinishBlackHeight5-7/8"Diameter3"OpticsReflective Cup Structure	Start Time	Instant
DimmingTriac Dimming / 0-10 V DimmingHeadsSingle HeadFinishBlackHeight5-7/8"Diameter3"OpticsReflective Cup Structure	Driver	Stand Alone (included)
HeadsSingle HeadFinishBlackHeight5-7/8"Diameter3"OpticsReflective Cup Structure	Operating Position	No Swiveling Type
FinishBlackHeight5-7/8"Diameter3"OpticsReflective Cup Structure	Dimming	Triac Dimming / 0-10 V Dimming
Height5-7/8"Diameter3"OpticsReflective Cup Structure	Heads	Single Head
Diameter 3" Optics Reflective Cup Structure	Finish	Black
Optics Reflective Cup Structure	Height	5-7/8"
	Diameter	3"
Application Area Guest Room, Restaurant, Meeting Room, Club, Hall, Hotel Entrance	Optics	Reflective Cup Structure
	Application Area	Guest Room, Restaurant, Meeting Room, Club, Hall, Hotel Entrance

Beam Spread (Options)

-			00.00	ion (opt	10110	/		
Spot 15		15°	Medium		30°	Flood	45°	
f	t		Ø	ft		Ø	ft	Ø
з	8.0		0.72	3.0		1.41	3.0	2.03
ę	0.0		2.15	9.0		4.22	9.0	6.09
1	5.0		3.58	15.0		7.04	15 <mark>.0</mark>	 10.15

Aurora is a technologically advanced LED Pendant Light that incorporates electronic gear and a high-quality lens with wide beam spread. While commonly used as task light, the unique and state-of-the-art design of this luminaire also enhances the overall aesthetics of your store.

retail@ikioledlighting.com | +1 844-533-4546 | www.retail.ikioledlighting.com

DIMMABLE

IP20

© IKIO LED LIGHTING 2025. All Rights Reserved. Products and technologies in this document may be covered by one or more Patents Pending. The product images shown are for illustration purposes only and may not be an exact representation of the product. Specifications subject to change without notice.

