



### Product Code : IK-RAuroraPL-15W-50K-BL-90C-15D

|                    |  |
|--------------------|--|
| Voltage            | 100 - 277 V AC, 50-60 Hz   |
| Lumen Output       | 1425lm   |
| Power              | 15W  |
| CCT                | 5000K  |
| CRI                | >90  |
| Beam Angle         | 15°  |
| Light Distribution | Spot   |
| LED Light Source   | Osram SOLERIQ S 19   |
| Start Time         | Instant  |
| Driver             | Stand Alone (included)   |
| Operating Position | No Swiveling Type  |
| Dimming            | Triac Dimming / 0-10 V Dimming                                   |
| Heads              | Single Head  |
| Finish             | Black  |
| Height             | 5-7/8"   |
| Diameter           | 3-3/4"   |
| Optics             | Reflective Cup Structure   |
| Application Area   | Guest Room, Restaurant, Meeting Room, Club, Hall, Hotel Entrance |

#### Beam Spread (Options)

| Spot | 15°  | Medium | 30°  | Flood | 45°   |
|------|------|--------|------|-------|-------|
| ft   | Ø    | ft     | Ø    | ft    | Ø     |
| 3.0  | 0.72 | 3.0    | 1.41 | 3.0   | 2.03  |
| 9.0  | 2.15 | 9.0    | 4.22 | 9.0   | 6.09  |
| 15.0 | 3.58 | 15.0   | 7.04 | 15.0  | 10.15 |

Aurora is a technologically advanced LED Pendant Light that incorporates electronic gear and a high-quality lens with wide beam spread. While commonly used as task light, the unique and state-of-the-art design of this luminaire also enhances the overall aesthetics of your store.

