

ITEM SKU#: 662187502212



COB LED

Product Code : IK-RAuroraPL-30W-27K-BL-90C-15D

Voltage 100 - 277 V AC, 50-60 Hz Lumen Output 2400Im Power 30W CCT 2700K CRI >90 Beam Angle 15° Light Distribution Spot
Power30WCCT2700KCRI>90Beam Angle15°
CCT 2700K CRI >90 Beam Angle 15°
CRI >90 Beam Angle 15°
Beam Angle 15°
Light Distribution Spot
LED Light Source Osram SOLERIQ S 19
Start Time Instant
Driver Stand Alone (included)
Operating Position No Swiveling Type
Dimming Triac Dimming / 0-10 V Dimming
Heads Single Head
Finish Black
Height 6-1/4"
Diameter 5-5/8"
Optics Reflective Cup Structure
Application Area Guest Room, Restaurant, Meeting Room, Club, Hall, Hotel Entrance

Beam Spread (Options)

Doarn oprodu (options)										
Spot		15°	Medium		30°	Flood		45°		
f	t		Ø	ft		Ø	ft		Ø	
з	8.0		0.72	3.0		1.41	3.0		2.03	
ę	0.0		2.15	9.0		4.22	9.0		6.09	
1	5.0		3.58	15.0		7.04	15 <mark>.0</mark>		10.15	

Aurora is a technologically advanced LED Pendant Light that incorporates electronic gear and a high-quality lens with wide beam spread. While commonly used as task light, the unique and state-of-the-art design of this luminaire also enhances the overall aesthetics of your store.

retail@ikioledlighting.com | +1 844-533-4546 | www.retail.ikioledlighting.com

DIMMABLE

IP20

© IKIO LED LIGHTING 2025. All Rights Reserved. Products and technologies in this document may be covered by one or more Patents Pending. The product images shown are for illustration purposes only and may not be an exact representation of the product. Specifications subject to change without notice.

