

ITEM SKU#: 662187502267



COB LED

## Product Code : IK-RAuroraPL-40W-30K-BL-90C-15D

Voltage100 - 277 V AC, 50-60 HzLumen Output3400lmPower40WCCT3000KCCT3000KCRI>90Beam Angle15°Light DistributionSpotLED Light SourceOsram SOLERIQ S 19Start TimeInstantDriverStand Alone (included)Operating PositionNo Swiveling TypeDimmingTriac Dimming / 0-10 V DimmingHeadsSingle HeadHeight61/4"Diameter5-5/8"OpticsMeet Room, Restaurant, Meeting Room, Club, Hall, Hotel Entrarce		
Power40WCCT3000KCRI>90Beam Angle15°Light DistributionSpotLED Light SourceOsram SOLERIQ S 19Start TimeInstantDriverStand Alone (included)Operating PositioNo Swiveling TypeImmingTriac Dimming / 0-10 V DimmingFinishBlackHeight6-1/4"Diameter5-5/8"OpticsReflective Cup Structure	Voltage	100 - 277 V AC, 50-60 Hz
FinancialReferenceCCT3000KCRI>90Beam Angle15°Light DistributionSpotLED Light SourceOsram SOLERIQ S 19Start TimeInstantDriverStand Alone (included)Operating PositionNo Swiveling TypeDimmingTriac Dimming / 0-10 V DimmingHeadsSingle HeadHeight6-1/4"Diameter5-5/8"OpticsReflective Cup Structure	Lumen Output	3400lm
CRI>90Beam Angle15°Light DistributionSpotLED Light SourceOsram SOLERIQ S 19Start TimeInstantDriverStand Alone (included)Operating PositionNo Swiveling TypeDimmingTriac Dimming / 0-10 V DimmingHeadsSingle HeadFinishBlackHeight6-1/4"Diameter5-5/8"OpticsReflective Cup Structure	Power	40W
Beam Angle15°Light DistributionSpotLED Light SourceOsram SOLERIQ S 19Start TimeInstantDriverStand Alone (included)Operating PositionNo Swiveling TypeDimmingTriac Dimming / 0-10 V DimmingHeadsSingle HeadFinishBlackHeight6-1/4"Diameter5-5/8"OpticsReflective Cup Structure	ССТ	3000K
Light DistributionSpotLED Light SourceOsram SOLERIQ S 19Start TimeInstantDriverStand Alone (included)Operating PositionNo Swiveling TypeDinmingTriac Dimming / 0-10 V DimmingHeadsSingle HeadFinishBlackHeight6-1/4"Diameter5-5/8"OpticsReflective Cup Structure	CRI	>90
LED Light SourceOsram SOLERIQ S 19Start TimeInstantDriverStand Alone (included)Operating PositionNo Swiveling TypeDimmingTriac Dimming / 0-10 V DimmingHeadsSingle HeadFinishBlackHeight6-1/4"Diameter5-5/8"OpticsReflective Cup Structure	Beam Angle	15°
Start TimeInstantDriverStand Alone (included)Operating PositionNo Swiveling TypeDimmingTriac Dimming / 0-10 V DimmingHeadsSingle HeadFinishBlackHeight6-1/4"Diameter5-5/8"OpticsReflective Cup Structure	Light Distribution	Spot
DriverStand Alone (included)Operating PositionNo Swiveling TypeDimmingTriac Dimming / 0-10 V DimmingHeadsSingle HeadFinishBlackHeight6-1/4"Diameter5-5/8"OpticsReflective Cup Structure	LED Light Source	Osram SOLERIQ S 19
Operating PositionNo Swiveling TypeDimmingTriac Dimming / 0-10 V DimmingHeadsSingle HeadFinishBlackHeight6-1/4"Diameter5-5/8"OpticsReflective Cup Structure	Start Time	Instant
DimmingTriac Dimming / 0-10 V DimmingHeadsSingle HeadFinishBlackHeight6-1/4"Diameter5-5/8"OpticsReflective Cup Structure	Driver	Stand Alone (included)
HeadsSingle HeadFinishBlackHeight6-1/4"Diameter5-5/8"OpticsReflective Cup Structure	Operating Position	No Swiveling Type
FinishBlackHeight6-1/4"Diameter5-5/8"OpticsReflective Cup Structure	Dimming	Triac Dimming / 0-10 V Dimming
Height6-1/4"Diameter5-5/8"OpticsReflective Cup Structure	Heads	Single Head
Diameter 5-5/8"   Optics Reflective Cup Structure	Finish	Black
Optics Reflective Cup Structure	Height	6-1/4"
	Diameter	5-5/8"
Application Area Guest Room, Restaurant, Meeting Room, Club, Hall, Hotel Entrance	Optics	Reflective Cup Structure
	Application Area	Guest Room, Restaurant, Meeting Room, Club, Hall, Hotel Entrance

## Beam Spread (Options)

Dealth Opread (options)										
	Spot		15°	Mediur	n	30°	Flood	45		
	ft		Ø	ft		Ø	ft	Ø		
	3.0		0.72	3.0		1.41	3.0	2.03		
	9.0		2.15	9.0		4.22	9.0	6.09		
	15.0		3.58	15.0		7.04	15 <mark>.0</mark>	10.15		

Aurora is a technologically advanced LED Pendant Light that incorporates electronic gear and a high-quality lens with wide beam spread. While commonly used as task light, the unique and state-of-the-art design of this luminaire also enhances the overall aesthetics of your store.

retail@ikioledlighting.com | +1 844-533-4546 | www.retail.ikioledlighting.com

DIMMABLE

IP20

© IKIO LED LIGHTING 2025. All Rights Reserved. Products and technologies in this document may be covered by one or more Patents Pending. The product images shown are for illustration purposes only and may not be an exact representation of the product. Specifications subject to change without notice.

