


Aurora Pendant Lights

ITEM SKU#: 662187502526













Product Code: IK-RAuroraPL-20W-50K-WH-90C-15D

| Voltage | 100 - 277 V AC, 50-60 Hz | | | | | | | |
|--------------------|------------------------------------------------------------------|--|--|--|--|--|--|--|
| Lumen Output | 1900lm | | | | | | | |
| Power | 20W | | | | | | | |
| ССТ | 5000K | | | | | | | |
| CRI | >90 | | | | | | | |
| Beam Angle | 15° | | | | | | | |
| Light Distribution | Spot | | | | | | | |
| LED Light Source | Osram SOLERIQ S 19 | | | | | | | |
| Start Time | Instant | | | | | | | |
| Driver | Stand Alone (included) | | | | | | | |
| Operating Position | No Swiveling Type | | | | | | | |
| Dimming | Triac Dimming / 0-10 V Dimming | | | | | | | |
| Heads | Single Head | | | | | | | |
| Finish | White | | | | | | | |
| Height 5-7/8" | | | | | | | | |
| Diameter | 4-1/2" | | | | | | | |
| Optics | Reflective Cup Structure | | | | | | | |
| Application Area | Guest Room, Restaurant, Meeting Room, Club, Hall, Hotel Entrance | | | | | | | |

| Beam Spread (Options) | | | | | | | | | | |
|-----------------------|--|------|-------|---|------|-------|--|-------|--|--|
| Spot | | 15° | Mediu | m | 30° | Flood | | 45° | | |
| ft | | Ø | ft | | Ø | ft | | Ø | | |
| 3.0 | | 0.72 | 3.0 | | 1.41 | 3.0 | | 2.03 | | |
| 9.0 | | 2.15 | 9.0 | | 4.22 | 9.0 | | 6.09 | | |
| 15.0 | | 3.58 | 15.0 | | 7.04 | 15.0 | | 10.15 | | |

Aurora is a technologically advanced LED Pendant Light that incorporates electronic gear and a high-quality lens with wide beam spread. While commonly used as task light, the unique and state-of-the-art design of this luminaire also enhances the overall aesthetics of your store.

