

ITEM SKU#: 662187502786



COB LED

Product Code : IK-RAuroraPL-12W-27K-BL-90C-30D

VoltageI00 - 277 V AC, 50-60 HzLumen Outputu960mPower12WPower270 KCCT>90CRI>90Beam Angle0°Light DistributusMediumModiumSora SOLERIQ S 19Start TimeInstantOperating PositusNoswieling TypeOperating PositusSingle HeadHadsaSingle HeadHeightSingle HeadDiameter3"OpticsMedive Cup StructureApplication ApplicationSingle Rest Cup StructureDiameterSingle StructureApplication ApplicationSingle Rest Cup StructureApplication ApplicationSingle Rest Cup StructureApplication ApplicationSingle Rest Cup StructureApplication Application Appli		
Power12WPower270KCCT270KCRI>90Bean Angle0°Light DistributionMediumKebustionSoran SOLERIQ S 19Start TimeStand Alone (included)DriverStand Alone (included)Operating PositionNisveling TypeHeadsSingle HeadFinsinBackFinsinSingle HeadFinghtSingle HeadDiameter3"OptionsBickStatterSingle HeadFinsinSingle HeadFinsin	Voltage	100 - 277 V AC, 50-60 Hz
NumeIntra-CCT2700KCRI>90Beam Angle30°Light DistributionMediumLED Light SourceOsram SOLERIQ S 19Start TimeInstantDriverStand Alone (included)Operating PositioNo Swiveling TypeImmingSingle HeadHeadsSingle HeadFinishBlackDiameter3"OpticsBeftetive Cup Structure	Lumen Output	960lm
RNCRI>90Beam Angle30°Light DistributionMediumLED Light SourceOsram SOLERIQ S 19Start TimeInstantDriverStand Alone (included)Operating PositioNoswiveling TypeDimmingTriac Dimming / 0-10 V DimmingHeadsSingle HeadFinishBlackHeight5-7/8"Diameter3"OpticsReflective Cup Structure	Power	12W
Beam Angle30°Light DistributionMediumLED Light SourceOram SOLERIQ S 19Start TimeInstantDriverStand Alone (included)Operating PositionNo Swiveling TypeDimmingTriac Dimming / 0-10 V DimmingHeadsSingle HeadFinishBlackHeight5-7/8"Diameter3"OpticsReflective Cup Structure	ССТ	2700К
Light DistributionMediumLED Light SourceOram SOLERIQ S 19Start TimeInstantDriverStand Alone (included)Operating PositionNo Swiveling TypeDinmingTriac Dimming / 0-10 V DimmingHeadsSingle HeadFinishBlackHeight5-7/8"Diameter3"OpticsReflective Cup Structure	CRI	>90
LED Light SoureOran SOLERIQ S 19Start TimeInstantDriverStand Alone (included)Operating PositioNo Swiveling TypeImmingTriac Dimming / 0-10 V DimmingHeadsSingle HeadFinishBlackHeight5-7/8"Diameter3"OpticsReflective Cup Structure	Beam Angle	30°
Start TimeInstantDriverStand Alone (included)Operating PositionNo Swiveling TypeDimmingTriac Dimming / 0-10 V DimmingHeadsSingle HeadFinishBlackHeight5-7/8"Diameter3"OpticsReflective Cup Structure	Light Distribution	Medium
AddressDriverStand Alone (included)Operating PositionNo Swiveling TypeDimmingTriac Dimming / 0-10 V DimmingHeadsSingle HeadFinishBlackHeight5-7/8"Diameter3"OpticsReflective Cup Structure	LED Light Source	Osram SOLERIQ S 19
Operating PositionNo Swiveling TypeDimmingTriac Dimming / 0-10 V DimmingHeadsSingle HeadFinishBlackHeight5-7/8"Diameter3"OpticsReflective Cup Structure	Start Time	Instant
DimmingTriac Dimming / 0-10 V DimmingHeadsSingle HeadFinishBlackHeight5-7/8"Diameter3"OpticsReflective Cup Structure	Driver	Stand Alone (included)
HeadsSingle HeadFinishBlackHeight5-7/8"Diameter3"OpticsReflective Cup Structure	Operating Position	No Swiveling Type
FinishBlackHeight5-7/8"Diameter3"OpticsReflective Cup Structure	Dimming	Triac Dimming / 0-10 V Dimming
Height5-7/8"Diameter3"OpticsReflective Cup Structure	Heads	Single Head
Diameter 3" Optics Reflective Cup Structure	Finish	Black
Optics Reflective Cup Structure	Height	5-7/8"
	Diameter	3"
Application Area Guest Room, Restaurant, Meeting Room, Club, Hall, Hotel Entrance	Optics	Reflective Cup Structure
	Application Area	Guest Room, Restaurant, Meeting Room, Club, Hall, Hotel Entrance

Beam Spread (Options)

		-		,			
Spot		15°	Medium	n	30°	Flood	45°
ft		Ø	ft		Ø	ft	Ø
3.0		0.72	3.0		1.41	3.0	2.03
9.0		2.15	9.0		4.22	9.0	6.09
15.0		3.58	15.0		7.04	15.0	10.15
	Spot ft 3.0 9.0	Spot ft 3.0 9.0	Spot 15° ft Ø 3.0 0.72 9.0 2.15	Spot 15° Medium ft Ø ft 3.0 0.72 3.0 9.0 2.15 9.0	Spot 15° Medium ft Ø ft 3.0 0.72 3.0 9.0 2.15 9.0	Spot 15° Medium 30° ft Ø ft Ø 3.0 0.72 3.0 1.41 9.0 2.15 9.0 4.22	ft Ø ft Ø ft 3.0 0.72 3.0 1.41 3.0 9.0 2.15 9.0 4.22 9.0

Aurora is a technologically advanced LED Pendant Light that incorporates electronic gear and a high-quality lens with wide beam spread. While commonly used as task light, the unique and state-of-the-art design of this luminaire also enhances the overall aesthetics of your store.

retail@ikioledlighting.com | +1 844-533-4546 | www.retail.ikioledlighting.com

DIMMABLE

IP20

© IKIO LED LIGHTING 2025. All Rights Reserved. Products and technologies in this document may be covered by one or more Patents Pending. The product images shown are for illustration purposes only and may not be an exact representation of the product. Specifications subject to change without notice.

