


# Aurora Pendant Lights



## Product Code : IK-RAuroraPL-12W-30K-WH-90C-45D

Voltage	100 - 277 V AC, 50-60 Hz
Lumen Output	1020lm
Power	12W
CCT	3000K
CRI	>90
Beam Angle	45°
Light Distribution	Flood
LED Light Source	Osram SOLERIQ S 19
Start Time	Instant
Driver	Stand Alone (included)
Operating Position	No Swiveling Type
Dimming	Triac Dimming / 0-10 V Dimming
Heads	Single Head
Finish	White
Height	5-7/8"
Diameter	3"
Optics	Reflective Cup Structure
Application Area	Guest Room, Restaurant, Meeting Room, Club, Hall, Hotel Entrance

### Beam Spread (Options)

Spot	15°		Medium		30°		Flood		45°	
	ft	Ø	ft	Ø	ft	Ø	ft	Ø	ft	Ø
3.0	0.72		3.0	1.41		3.0	2.03			
9.0	2.15		9.0	4.22		9.0	6.09			
15.0	3.58		15.0	7.04		15.0	10.15			

Aurora is a technologically advanced LED Pendant Light that incorporates electronic gear and a high-quality lens with wide beam spread. While commonly used as task light, the unique and state-of-the-art design of this luminaire also enhances the overall aesthetics of your store.

