



Product Code : IK-REosPL-30W-27K-BL-90C-45D

| | |
|--------------------|--|
| Voltage | 100 - 277 V AC, 50-60 Hz |
| Lumen Output | 2400lm |
| Power | 30W |
| CCT | 2700K |
| CRI | >90 |
| Beam Angle | 45° |
| Light Distribution | Flood |
| LED Light Source | Osram SOLERIQ S 19 |
| Start Time | Instant |
| Driver | Stand Alone (included) |
| Operating Position | No Swiveling Type |
| Dimming | Triac Dimming / 0-10 V Dimming |
| Heads | Single Head |
| Finish | Black |
| Length | 4-1/2" |
| Height | 6-1/4" |
| Optics | Reflective Cup Structure |
| Width (W) | 4-1/2" |
| Application Area | Guest Room, Restaurant, Meeting Room, Club, Hall, Hotel Entrance |

Beam Spread (Options)

| Spot | 15° | Medium | 30° | Flood | 45° |
|------|------|--------|------|-------|-------|
| ft | Ø | ft | Ø | ft | Ø |
| 3.0 | 0.72 | 3.0 | 1.41 | 3.0 | 2.03 |
| 9.0 | 2.15 | 9.0 | 4.22 | 9.0 | 6.09 |
| 15.0 | 3.58 | 15.0 | 7.04 | 15.0 | 10.15 |

Eos is a technologically advanced LED Pendant Light that incorporates electronic gear and a high-quality lens with wide beam spread. While commonly used as task light, the unique and state-of-the-art design of this luminaire also enhances the overall aesthetics of your store.

