



## Product Code : IK-RTRANGTL-30W-30/40/50K-BL-90C-60D

Voltage	100 - 277 V AC, 50-60 Hz
Lumen Output	2733.3lm
Power	30W
Efficacy	90lm/w
CCT Selectable(K)	3000- 4000- 5000K
CRI	>90
Beam Angle	60°
Light Distribution	Wide flood
LED Type	COB
LED Light Source	Osram SOLERIQ S 19
Start Time	Instant
Driver	Stand Alone (included)
Operating Position	Swiveling Type
Dimming	Triac Dimming
Construction	Track
Mounting Type	Track Light Structure
Heads	Single Head
Body Material	Aluminium Die cast
Finish	Black
Length	6-7/8"
Height	7-1/8"
Diameter	3"
Application Area	Indoor Applications



Trang is a technologically advanced LED track light with incorporated electronic gear and chip on board. It also has a high-quality reflector with three different beam spreads. Moreover, the lamp housing of die-cast aluminum for optimal cooling allows the fixture to last longer than its traditional counterparts.

### Beam Spread (Options)

Spot	15°		Medium		24°		Flood		38°		Wide Flood		60°	
	ft	Ø	ft	Ø	ft	Ø	ft	Ø	ft	Ø	ft	Ø	ft	Ø
3.0	0.72	3.0	1.41	3.0	2.03	3.0	3.15	3.0	3.15	3.0	3.15	3.0	3.15	3.0
9.0	2.15	9.0	4.22	9.0	6.09	9.0	9.45	9.0	9.45	9.0	9.45	9.0	9.45	9.0
15.0	3.58	15.0	7.04	15.0	10.15	15.0	15.75	15.0	15.75	15.0	15.75	15.0	15.75	15.0

### Technical Data

[↓ IES File Link](#)

[↓ Installation Instructions Link](#)